PACIFIC RIM INDUSTRIES

PRO-FLOOR LIGHT WEIGHT

Pro-Floor Light Weight cement flooring panels are manufactured in accordance to ASNZS 2908.2 Type A, category 3.

It is intended for general purpose construction in residential and light commercial situations for durable and non-combustible floor platforms.

This guide is intended for general purposes and cannot anticipate all situations. Pro-Floor Light Weight flooring should be designed and constructed in conformance to AS/NZS 1170.1 Structural design actions: Part 1: Permanent, imposed and other actions.

It is the designer's responsibility to:

1. Ensure that the supporting structure is adequate for the anticipated loads and general requirements in the structure.

1. To determine that the specifications of this product are suitable for the intended end use applications to meet with the relevant sections of the National Construction Code

LENGTH & WIDTH (mm)	THICKNESS (mm)	APPROX WEIGHT PER SHEET (kg)	APPROX WEIGHT PER m2 (kg)
2700 x 600	19	43	26.5

For the correct installation of fibre cement sheet flooring:

1. The installer should at a minimum be competent in general construction and working with fibre cement products.

2. Competency in working with power tools such as circular saw and drill will also be required.

STORAGE

PRO-FLOOR Light weight- should be stored dry, flat and with all edges protected from damage. We recommend storage undercover and raised from the ground.

PRO-FLOOR Light Weight contains less than 1% crystalline silica.

